



---

# OSLC Change Management Version 3.0. Part 1: Specification

## Committee Specification 02

24 August 2018

### Specification URIs

#### This version:

<http://docs.oasis-open.org/oslc-domains/cm/v3.0/cs02/part1-change-mgt/cm-v3.0-cs02-part1-change-mgt.html> (Authoritative)  
<http://docs.oasis-open.org/oslc-domains/cm/v3.0/cs02/part1-change-mgt/cm-v3.0-cs02-part1-change-mgt.pdf>

#### Previous version:

<http://docs.oasis-open.org/oslc-domains/cm/v3.0/cs01/part1-change-mgt/cm-v3.0-cs01-part1-change-mgt.html> (Authoritative)  
<http://docs.oasis-open.org/oslc-domains/cm/v3.0/cs01/part1-change-mgt/cm-v3.0-cs01-part1-change-mgt.pdf>

#### Latest version:

<http://docs.oasis-open.org/oslc-domains/cm/v3.0/cm-v3.0-part1-change-mgt.html> (Authoritative)  
<http://docs.oasis-open.org/oslc-domains/cm/v3.0/cm-v3.0-part1-change-mgt.pdf>

#### Technical Committee:

[OASIS OSLC Lifecycle Integration Domains TC](#)

#### Chairs:

Jim Amsden ([jamsden@us.ibm.com](mailto:jamsden@us.ibm.com)), [IBM](#)  
Graham Bachelor ([gray\\_bachelor@uk.ibm.com](mailto:gray_bachelor@uk.ibm.com)), [IBM](#)

**Editor:**

Jim Amsden ([jamsden@us.ibm.com](mailto:jamsden@us.ibm.com)), [IBM](#)

**Additional artifacts:**

This specification is one component of a Work Product that also includes:

- *OSLC Change Management Version 3.0. Part 1: Specification (this document)*. <http://docs.oasis-open.org/oslc-domains/cm/v3.0/cs02/part1-change-mgt/cm-v3.0-cs02-part1-change-mgt.html>
- *OSLC Change Management Version 3.0. Part 2: Vocabulary*. <http://docs.oasis-open.org/oslc-domains/cm/v3.0/cs02/part2-change-mgt-vocab/cm-v3.0-cs02-part2-change-mgt-vocab.html>

**Related work:**

This specification is related to:

- *Open Services for Lifecycle Collaboration Change Management Specification Version 2.0*. <http://open-services.net/bin/view/Main/CmSpecificationV2>

**RDF Namespaces:**

<http://open-services.net/ns/cm#>

**Abstract:**

This specification defines the OSLC Change Management domain, a RESTful web services interface for the management of product change requests, activities, tasks and relationships between those and related resources such as requirements, test cases, or architectural resources. To support these scenarios, this specification defines a set of HTTP-based RESTful interfaces in terms of HTTP methods: GET, POST, PUT and DELETE, HTTP response codes, content type handling and resource formats.

**Status:**

This document was last revised or approved by the [OASIS OSLC Lifecycle Integration Domains TC](#) on the above date. The level of approval is also listed above. Check the “Latest version” location noted above for possible later revisions of this document. Any other numbered Versions

and other technical work produced by the Technical Committee (TC) are listed at [https://www.oasis-open.org/committees/tc\\_home.php?wg\\_abbrev=oslc-domains#technical](https://www.oasis-open.org/committees/tc_home.php?wg_abbrev=oslc-domains#technical).

TC members should send comments on this specification to the TC's email list. Others should send comments to the TC's public comment list [oslc-domains-comment@lists.oasis-open.org](mailto:oslc-domains-comment@lists.oasis-open.org), after subscribing to it by following the instructions at the "Send A Comment" button on the TC's web page at <https://www.oasis-open.org/committees/oslc-domains/>.

This specification is provided under the [RF on Limited Terms](#) Mode of the [OASIS IPR Policy](#), the mode chosen when the Technical Committee was established. For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the TC's web page (<https://www.oasis-open.org/committees/oslc-domains/ipr.php>).

Note that any machine-readable content ([Computer Language Definitions](#)) declared Normative for this Work Product is provided in separate plain text files. In the event of a discrepancy between any such plain text file and display content in the Work Product's prose narrative document(s), the content in the separate plain text file prevails.

#### Citation format:

When referencing this specification the following citation format should be used:

#### **[OSLC-CM-3.0-Part1]**

*OSLC Change Management Version 3.0. Part 1: Specification*. Edited by Jim Amsden. 24 August 2018. OASIS Committee Specification 02 <http://docs.oasis-open.org/oslc-domains/cm/v3.0/cs02/part1-change-mgt/cm-v3.0-cs02-part1-change-mgt.html>. Latest version: <http://docs.oasis-open.org/oslc-domains/cm/v3.0/cm-v3.0-part1-change-mgt.html>.

---

## Notices

Copyright © OASIS Open 2018. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](https://www.oasis-open.org/), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark> for above guidance.

---

# Table of Contents

1. Introduction .....	7
1.1 IPR Policy .....	7
1.2 Terminology .....	7
1.3 References .....	8
1.3.1 Normative references .....	8
1.3.2 Informative references .....	8
1.4 Typographical Conventions and Use of RFC Terms .....	9
2. Base Requirements .....	10
2.1 Base Compliance .....	10
2.2 Specification Versioning .....	12
2.3 Namespaces .....	12
2.4 Resource Formats .....	12
2.4.1 Content Negotiation .....	13
2.5 Authentication .....	14
2.6 Error Responses .....	14
2.7 Pagination .....	14
2.8 Requesting and Updating Properties .....	14
2.8.1 Requesting a Subset of Properties .....	14
2.8.2 Updating a Subset of Properties .....	14
2.8.3 Updating Multi-Valued Properties .....	15
2.9 Status, State and State Predicates .....	15
2.10 Labels for Relationships .....	15
3. Vocabulary Terms and Constraints .....	18
4. CM Server Capabilities .....	19
4.1 Server Resources .....	19
4.2 Creation Factories .....	19
4.3 Query Capabilities .....	19
4.4 Delegated UIs .....	20
4.5 Usage Identifiers .....	20
5. Conformance .....	21
Appendix A. Version Compatibility with 2.0 Specifications .....	26
A.1 Deprecated terms .....	26
A.2 Changes from 2.0 .....	28
Appendix B. Acknowledgements .....	29
Appendix C. Change History .....	30

---

# 1. Introduction

*This section is non-normative.*

This specification defines the OSLC Change management domain as a RESTful web services interface for the management of product change requests, activities, tasks and relationships between those and related resources such as project, category, release and plan. To support these scenarios, this specification defines a set of HTTP-based RESTful interfaces in terms of HTTP methods: GET, POST, PUT and DELETE, HTTP response codes, content type handling and resource formats.

The intent of this specification is to define the capabilities needed to support integration scenarios defined by the Change Management Technical Committee and not to provide a comprehensive interface to Change Management. The resource formats and operations may not match exactly the native models supported by change management servers but are intended to be compatible with them. The approach to supporting these scenarios is to delegate operations, as driven by server contributed user interfaces, as much as possible and not require a server to expose its complete data model and application logic.

## 1.1 IPR Policy

This specification is provided under the [RF on Limited Terms](#) Mode of the [OASIS IPR Policy](#), the mode chosen when the Technical Committee was established. For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the TC's web page (<https://www.oasis-open.org/committees/oslc-domains/ipr.php>).

## 1.2 Terminology

Terminology uses and extends the terminology and capabilities of [[OSLCCore3](#)].

### Change Request Resource

A request for change to an application or product. Typically a product request for enhancement, a report for a resolution of a product defect or simply a bug report.

### Client

An implementation of the OSLC Change Management specifications as a client. OSLC CM Clients consume services provided by servers.

### Server

An implementation of the OSLC Change Management specifications as a server. OSLC CM clients consume services provided by Servers. The use of the terms Client and Server are intended to distinguish typical consumers and providers of OSLC resources in a distributed environment based on REST. A particular application component could be a client for some OSLC domain services and a server for the same or another domain.

## 1.3 References

### 1.3.1 Normative references

[OSLCCore2]

S. Speicher; D. Johnson. *OSLC Core 2.0*. Finalized. URL: <http://open-services.net/bin/view/Main/OslcCoreSpecification>

[OSLCCore3]

Jim Amsden; S. Speicher. *OSLC Core 3.0*. Committee Specification. URL: <http://docs.oasis-open.org/oslc-core/oslc-core/v3.0/oslc-core-v3.0-part1-overview.html>

[OSLCCoreVocab]

Jim Amsden; S. Padgett; S. Speicher. *OSLC Core Vocabulary*. Working Draft. URL: <http://docs.oasis-open.org/oslc-core/oslc-core/v3.0/oslc-core-v3.0-part7-core-vocabulary.html>

[OSLCResourcePreview]

Jim Amsden; S. Speicher. *OSLC Core 3.0 Resource Preview*. Draft. URL: <http://docs.oasis-open.org/oslc-core/oslc-core/v3.0/oslc-core-v3.0-part3-resource-preview.html>

[OSLCShapes]

Arthur Ryman; Jim Amsden. *OSLC Resource Shape 3.0*. URL: <http://docs.oasis-open.org/oslc-core/oslc-core/v3.0/oslc-core-v3.0-part6-resource-shape.html>

[OpenIDConnect]

*OpenID Connect*. URL: <http://openid.net/connect/>

[RFC2119]

S. Bradner. *Key words for use in RFCs to Indicate Requirement Levels*. March 1997. Best Current Practice. URL: <https://tools.ietf.org/html/rfc2119>

### 1.3.2 Informative references

[LDPPatch]

*Linked Data Patch Format*. Working Group Note. URL: <http://www.w3.org/TR/ldpatch/>

[OSLCActions]

Martin Pain; Steve Speicher. *Open Services for Lifecycle Collaboration Actions Specification Version 2.0*. Finalization. URL: <http://open-services.net/wiki/core/Actions-2.0/>



[OSLCCM20]

S. Speicher. [Open Services for Lifecycle Collaboration Change Management Specification Version 2.0](http://open-services.net/bin/view/Main/CmSpecificationV2). Finalized. URL: <http://open-services.net/bin/view/Main/CmSpecificationV2>

[OSLCQM]

Paul McMahan. [Open Services for Lifecycle Collaboration Quality Management Specification Version 2.0](http://open-services.net/bin/view/Main/QmSpecificationV2). Final. URL: <http://open-services.net/bin/view/Main/QmSpecificationV2>

[OSLCRM]

Ian Green. [Open Services for Lifecycle Collaboration Requirements Management Specification Version 2.0](http://open-services.net/bin/view/Main/RmSpecificationV2). Final. URL: <http://open-services.net/bin/view/Main/RmSpecificationV2>

## 1.4 Typographical Conventions and Use of RFC Terms

As well as sections marked as non-normative, all authoring guidelines, diagrams, examples, and notes in this specification are non-normative. Everything else in this specification is normative.

The key words **MUST**, **MUST NOT**, **REQUIRED**, **SHOULD**, **SHOULD NOT**, **RECOMMENDED**, **MAY**, and **OPTIONAL** in this specification are to be interpreted as described in [RFC2119].

---

## 2. Base Requirements

The following sub-sections define the mandatory and optional requirements for an OSLC Requirements Management (OSLC RM) server.

### 2.1 Base Compliance

This specification is based on [OSLCCore3]. OSLC CM servers **MUST** be compliant with both the core specification, **MUST** follow all the mandatory requirements in the normative sections of this specification, and **SHOULD** follow all the guidelines and recommendations in both these specifications. [CC-1]

An OSLC CM server **MUST** implement the domain vocabulary defined in [OSLC Change Management Version 3.0. Part 2: Vocabulary](#) [CC-2]

The following table summarizes the requirements from OSLC Core Specification as well as some additional requirements specific to the CM domain. Note that this specification further restricts some of the requirements for OSLC Core Specification. See the previous sections in this specification or the OSLC Core Specification to get further details on each of these requirements.

Requirement	Meaning
Unknown properties and content	OSLC servers <b>MAY</b> ignore unknown content and OSLC clients <b>MUST</b> preserve unknown content [CC-3]
Resource Operations	OSLC service <b>MUST</b> support resource operations via standard HTTP operations [CC-4]
Resource Paging	OSLC servers <b>MAY</b> provide paging for resources but only when specifically requested by client [CC-5]
Partial Resource Representations	OSLC servers <b>MUST</b> support request for a subset of a resource's properties via the oslc.properties URL parameter retrieval via HTTP GET [CC-6]
Partial Update	OSLC servers <b>MAY</b> support partial update of resources using [LDPPatch], or via HTTP PUT. [CC-7]
Discovery	OSLC servers <b>SHOULD</b> provide a ServiceProvider resource for Core v2 compatibility, <b>MAY</b> provide a ServiceProviderCatalog, and <b>MAY</b> provide other forms of discovery described in Core 3.0 Discovery. [CC-8]

Requirement	Meaning
Creation Factories	OSLC servers <b>MUST</b> provide LDPC creation factories to enable resource creation of Change Management resources via HTTP POST <a href="#">[CC-9]</a>
Query Capabilities	OSLC servers <b>SHOULD</b> provide query capabilities to enable clients to query for resources <a href="#">[CC-10]</a>
Query Syntax	OSLC query capabilities <b>SHOULD</b> support the OSLC Core Query Syntax and <b>MAY</b> use other query syntax <a href="#">[CC-11]</a>
Delegated UI Dialogs	OSLC Services <b>MUST</b> offer delegated UI dialogs (creation and selections) specified via OSLC Core 3.0 Delegated Dialogs and <b>SHOULD</b> include discovery through a ServiceProvider resource for OSLC v2 compatibility <a href="#">[CC-12]</a>
UI Preview	OSLC Services <b>SHOULD</b> offer UI previews for resources that may be referenced by other resources specified via OSLC Core 3.0 Preview and <b>SHOULD</b> include discovery through a server resource for OSLC v2 compatibility <a href="#">[CC-13]</a>
Authentication	OSLC Services <b>SHOULD</b> follow the recommendations for Authentication specified in <a href="#">[OSLCCore3]</a> <a href="#">[CC-14]</a>
Error Responses	OSLC Services <b>SHOULD</b> provide error responses using OSLC Core 3.0 defined error formats <a href="#">[CC-15]</a>
Turtle Representations	OSLC servers <b>MUST</b> provide a Turtle representation for HTTP GET requests and <b>SHOULD</b> support Turtle representations on POST and PUT requests. <a href="#">[CC-16]</a>
RDF/XML Representations	OSLC servers <b>SHOULD</b> provide an RDF/XML representation for HTTP GET requests and <b>SHOULD</b> support RDF/XML representations on POST and PUT requests for compatibility with Change Management 2.0. <a href="#">[CC-17]</a>
XML Representations	OSLC servers <b>SHOULD</b> provide a XML representation for HTTP GET, POST and PUT requests that conform to the Core 2.0 Guidelines for XML. <a href="#">[CC-18]</a>
JSON Representations	OSLC servers <b>MUST</b> provide JSON-LD representations for HTTP GET, POST and PUT requests that conform to the Core Guidelines for JSON-LD <a href="#">[CC-19]</a>

Requirement	Meaning
HTML Representations	OSLC servers <b>SHOULD</b> provide HTML representations for HTTP GET requests <a href="#">[CC-20]</a>

## 2.2 Specification Versioning

This specification follows the specification version guidelines given in [\[OSLCCore3\]](#).

## 2.3 Namespaces

In addition to the namespace URIs and namespace prefixes `oslc`, `rdf`, `dcterms` and `foaf` defined in the [\[OSLCCore3\]](#), OSLC CM defines the namespace URI of `http://open-services.net/ns/cm#` with a namespace prefix of `oslc_cm`.

This specification also uses these namespace prefix definitions:

- `oslc_rm` : `http://open-services.net/ns/rm#` [\[OSLCRM\]](#)
- `oslc_qm` : `http://open-services.net/ns/qm#` [\[OSLCQM\]](#)

## 2.4 Resource Formats

In addition to the requirements for resource representations in [\[OSLCCore3\]](#), this section outlines further refinements and restrictions.

For HTTP GET requests on all OSLC CM and OSLC Core defined resource types,

- CM servers **MUST** provide Turtle and JSON-LD, and **SHOULD** provide RDF/XML and XML representations. The XML and JSON representations **SHOULD** follow the guidelines outlined in the [OSLC Core Representations Guidance](#) to maintain compatibility with [\[OSLCCore2\]](#). [\[CC-21\]](#)
- CM clients requesting RDF/XML **SHOULD** be prepared for any valid RDF/XML document. CM clients requesting XML **SHOULD** be prepared for representations that follow the guidelines outlined in the [OSLC Core Representations Guidance](#). [\[CC-22\]](#)
- CM servers **SHOULD** support an [X]HTML representation and a user interface (UI) preview as defined by [UI Preview Guidance](#) [\[CC-23\]](#)

For HTTP PUT/POST request formats for resource type of ChangeRequest:

- CM servers **MUST** accept Turtle and JSON-LD representations and **SHOULD** accept RDF/XML and XML representations. CM servers accepting RDF/XML **SHOULD** be prepared for any valid RDF/XML

document. For XML CM servers **SHOULD** be prepared for representations that follow the guidelines outlined in the [OSLC Core Representations Guidance](#). [CC-24]

For HTTP GET response formats for Query requests,

CM servers **MUST** provide Turtle and JSON-LD, **SHOULD** provide RDF/XML, XML, and **MAY** provide Atom Syndication Format XML representations. [CC-25]

When CM clients request:

- `text/turtle` CM servers **MUST** respond with Turtle representation. [CC-26]
- `application/ld+json` CM servers **MUST** respond with JSON-LD representation. [CC-27]
- `application/rdf+xml` CM servers **SHOULD** respond with RDF/XML representation without restrictions. [CC-28]
- `application/xml` CM servers **SHOULD** respond with OSLC-defined abbreviated XML representation as defined in the [OSLC Core Representations Guidance](#) [CC-29]
- `application/atom+xml` CM servers **SHOULD** respond with Atom Syndication Format XML representation as defined in the [OSLC Core Representations Guidance](#) [CC-30]
- The Atom Syndication Format XML representation **SHOULD** use RDF/XML representation without restrictions for the `atom:content` entries representing the resource representations. [CC-31]

See Query Capabilities for additional information when Resource Shapes affect representation.

#### 2.4.1 Content Negotiation

[OSLCCore3] specifies RDF representations (and specifically Turtle and JSON-LD) as a convention that all OSLC server implementations minimally provide and accept. OSLC CM server implementations are strongly encouraged to adopt this convention. Future versions of this specification are expected to require RDF representations for all operations and relax requirements for specialized XML representations.

**XML Representation** - identified by the `application/xml` content type. Format representation rules are outlined in Core [OSLC Core Resource Formats section](#)

**RDF/XML Representation** - identified by the `application/rdf+xml` content type. No additional guidance is given.

**JSON-LD Representation** - identified by the `application/ld+json` content type. Format representation rules are specified in [JSON-LD 1.0](#).

**Atom Syndication Format XML Representation** - identified by the `application/atom+xml` content type. Format representation rules are outlined in Core [OSLC Core Resource Formats section](#).

## 2.5 Authentication

[[OSLCCore3](#)] specifies the recommended OSLC authentication mechanisms. In addition to the OSLC Core authentication requirements, OSLC CM servers **SHOULD** support [[OpenIDConnect](#)]. [[CC-32](#)]

## 2.6 Error Responses

[[OSLCCoreVocab](#)] specifies the OSLC Core error responses. OSLC CM puts no additional constraints on error responses.

## 2.7 Pagination

OSLC CM servers **SHOULD** support pagination of query results and **MAY** support pagination of a single resource's properties as defined by [[OSLCCore3](#)]. [[CC-33](#)]

## 2.8 Requesting and Updating Properties

### 2.8.1 Requesting a Subset of Properties

A client **MAY** request a subset of a resource's properties as well as properties from a referenced resource. In order to support this behavior a server **MUST** support the `oslc.properties` and `oslc.prefix` URL parameter on a HTTP GET request on individual resource request or a collection of resources by query. If the `oslc.properties` parameter is omitted on the request, then all resource properties **MUST** be provided in the response. [[CC-34](#)]

### 2.8.2 Updating a Subset of Properties

A client **MAY** request that a subset of a resource's properties be updated by using the [[LDPPatch](#)] `PATCH` method. [[CC-35](#)]

For compatibility with [[OSLCCore2](#)], CM servers **MAY** also support partial update by identifying those properties to be modified using the `oslc.properties` URL parameter on a HTTP PUT request. [[CC-36](#)]

If the parameter `oslc.properties` contains a valid resource property on the request that is not provided in the content, the server **MUST** set the resource's property to a null or empty value. If the parameter `oslc.properties` contains an invalid resource property, then a 409 Conflict **MUST** be returned. [CC-37]

### 2.8.3 Updating Multi-Valued Properties

For multi-valued properties that contain a large number of values, it may be difficult and inefficient to add or remove property values. OSLC CM servers **MAY** provide support for a partial update of the multi-valued properties as defined by draft specification [LDPPatch]. CM servers **MAY** also support partial updates through HTTP PUT where only the updated properties are included in the entity request body. [CC-38]

## 2.9 Status, State and State Predicates

Probably the most important property of a Change Request is the status property. "Status" specifies the location of a Change Request in a workflow. The `oslc_cm:status` property is a typically read-only string that servers can set to describe the status of a ChangeRequest. In queries the `oslc_cm:status` property can be used to filter change request (e.g. all change requests that are "fixed") and may be used to perform state transitions (not part of this specification) on a change request, e.g. closing a change request as "fixed".

The problem is that different CM servers may use different properties (or even a set of properties) and different values to represent the change request's state. Even providing access to meta data does not help because knowing all possible state values does not reveal the semantics of a state.

[OSLCCM20] introduced State Predicates to define single-value often read-only Boolean properties on a Change Request resource that allow servers to translate their specific status string values into a standard boolean state predicate value. An attempt to update read-only predicates **SHOULD** be answered with a 409 Conflict HTTP status code. Their presence in a resource representation used for an update via PUT **MUST NOT** prevent the resource from being updated. Predicates **MUST** be queryable. The Change Request resource definition sections defines the complete set of predicates. [CC-39]

OSLC CM 3.0 provides a similar means of defining a set of standard states that is also extensible. The `oslc_cm:state` property can have a value of type `oslc_cm:State` which represents an enumeration of individuals representing a standard set of ChangeRequest states. Servers **MAY** define additional individuals to extend the states of different ChangeRequest types and lifecycles. [CC-40]

## 2.10 Labels for Relationships



*This section is non-normative.*

Change Management relationships to other resources are represented by RDF properties. Instances of a relationship - often called links - are RDF triples with a subject URI, a predicate that is the property, and a value (or object) that is the URI of target resource. When a link is to be presented in a user interface, it may be helpful to display an informative and useful textual label instead of or in addition to the URI of the predicate and or object. There are three items that clients could display:

- **The property:** OSLC recommends using the `rdfs:label` property of the `rdf:Property` from the vocabulary to display the property.
- **The value, or object of the triple:** OSLC recommends using OSLC resource preview [[OSLCResourcePreview](#)] to obtain an appropriate icon and label, and possibly a small and/or large dialog for displaying the object.
- **The link:** The link is a combination of the subject, predicate and object of the triple (RDF statement or assertion). In the case where the link requires a unique label that is not available from the target resource, only then OSLC servers may support a `dcterms:title` on a reified statement to provide a label for a link that describes the assertion itself.

Turtle example using a reified statement:

#### EXAMPLE 1

```
@prefix ns0: <http://open-services.net/ns/cm#> .
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
@prefix dcterms: <http://purl.org/dc/terms/> .

<http://example.com/bugs/4321>
  a <http://open-services.net/ns/cm#ChangeRequest> ;
  ns0:relatedChangeRequest <http://anotherexample.com/defects/123> .

<http://njh.me/#link1>
  a rdf:Statement ;
  rdf:subject <http://example.com/bugs/4321> ;
  rdf:predicate ns0:relatedChangeRequest ;
  rdf:object <http://anotherexample.com/defects/123> ;
  dcterms:title "Defect 123: Problems during install" .
```

JSON-LD example using reified statement:

#### EXAMPLE 2

```
{
  "@context": {
    "dcterms": "http://purl.org/dc/terms/",
    "rdf": "http://www.w3.org/1999/02/22-rdf-syntax-ns#",
    "oslc": "http://open-services.net/ns/core#",
    "oslc_cm": "http://open-services.net/ns/cm#"
  },
```



```
"@id": "http://example.com/bugs/4321",
"@type": "oslc_cm:ChangeRequest",
"oslc_cm:relatedChangeRequest": {
  "@id": "http://anotherexample.com/defects/123",
  "dcterms:title": "Defect 123: Problems during install"
}
}
```

---

## 3. Vocabulary Terms and Constraints

[OSLC Change Management Version 3.0. Part 2: Vocabulary](#) Defines the vocabulary terms and constraints for OSLC Change Management resources. These terms and constraints are specified according to [[OSLCCoreVocab](#)]. [CC-41]

---

## 4. CM Server Capabilities

### 4.1 Server Resources

OSLC CM servers **MUST** support OSLC Discovery capabilities defined by [OSLCCore3]. [CC-42]

OSLC CM servers **MAY** provide a ServiceProvider Resource that can be retrieved at a implementation dependent URI. [CC-43]

OSLC CM servers **MAY** provide a ServiceProviderCatalog Resource that can be retrieved at a implementation dependent URI. [CC-44]

OSLC CM servers **MAY** provide a `oslc:serviceProvider` property for their defined resources that will be the URI to a ServiceProvider Resource. [CC-45]

OSLC CM servers **MUST** supply a value of `http://open-services.net/ns/cm#` for the property `oslc:domain` on either `oslc:Service` or `oslc:ServiceProviderCatalog` resources. [CC-46]

OSLC CM servers **MAY** allow ChangeRequest state change through [OSLCActions]. [CC-47]

### 4.2 Creation Factories

OSLC CM servers **MUST** support [Creation Factories](#) and list them in the Service Provider Resource as defined by OSLC Core. OSLC CM servers **SHOULD** support Resource Shapes for Creation Factories as defined in [OSLCShapes] [CC-48]

### 4.3 Query Capabilities

OSLC CM servers **SHOULD** support the [Query Capabilities](#) as defined by [OSLCCore3]. OSLC CM servers **SHOULD** support Resource Shapes for Query Capability as defined in [OSLCShapes] [CC-49]

The Query Capability, if supported, **MUST** support these parameters: [CC-50]

- `oslc.where`
- `oslc.select`
- `oslc.properties`
- `oslc.prefix`

If shape information is NOT present with the Query Capability, servers **SHOULD** use these default properties to contain the result: [CC-51]

- For RDF/XML and XML, use `rdf:Description` and `rdfs:member` as defined in [OSLC Core RDF/XML Examples](#).
- For JSON, the query results are contained within `oslc:results` array. See [OSLC Core Representation Guidance for JSON](#)

## 4.4 Delegated UIs

OSLC CM servers **MUST** support the selection and creation of resources by delegated web-based user interface dialogs [Delegated UIs](#) as defined by [OSLC Core3]. [CC-52]

OSLC CM servers **MAY** support the pre-filling of creation dialogs based on the definition at [Delegated UIs](#). [CC-53]

## 4.5 Usage Identifiers

An OSLC CM server **MAY** identify or distinguish the usage of various services with additional property values for the [OSLC Core](#) defined `oslc:usage` property on `oslc:Dialog`, `CreationFactory` and `QueryCapability`. The `oslc:usage` property value of `http://open-services.net/ns/core#default` will be used to designate the default or primary service to be used by clients when multiple entries are found. [CC-54]

The additional Change Management property values for `oslc:usage` are:

- `http://open-services.net/ns/cm#defect` - primarily used by QM tools to report defects in testing.
- `http://open-services.net/ns/cm#planItem` - used by QM and PPM tools for associating change requests into plans (project, release, sprint, etc).
- `http://open-services.net/ns/cm#task` - used by QM and PPM tools for associating change requests into executable and track-able items.
- `http://open-services.net/ns/cm#requirementsChangeRequest` - used by RM tools for associating a change request for usage in tracking changes to a Requirements resource

---

## 5. Conformance

Implementations of this specification need to satisfy the following conformance clauses.

Clause Number	Requirement
<a href="#">CC-1</a>	This specification is based on [ <a href="#">OSLCCore3</a> ]. OSLC CM servers <b>MUST</b> be compliant with both the core specification, <b>MUST</b> follow all the mandatory requirements in the normative sections of this specification, and <b>SHOULD</b> follow all the guidelines and recommendations in both these specifications.
<a href="#">CC-2</a>	An OSLC CM server <b>MUST</b> implement the domain vocabulary defined in <a href="#">OSLC Change Management Version 3.0. Part 2: Vocabulary</a>
<a href="#">CC-3</a>	OSLC servers <b>MAY</b> ignore unknown content and OSLC clients <b>MUST</b> preserve unknown content
<a href="#">CC-4</a>	OSLC service <b>MUST</b> support resource operations via standard HTTP operations
<a href="#">CC-5</a>	OSLC servers <b>MAY</b> provide paging for resources but only when specifically requested by client
<a href="#">CC-6</a>	OSLC servers <b>MUST</b> support request for a subset of a resource's properties via the oslc.properties URL parameter retrieval via HTTP GET
<a href="#">CC-7</a>	OSLC servers <b>MAY</b> support partial update of resources using [ <a href="#">LDPPatch</a> ], or via HTTP PUT.
<a href="#">CC-8</a>	OSLC servers <b>SHOULD</b> provide a ServiceProvider resource for Core v2 compatibility, <b>MAY</b> provide a ServiceProviderCatalog, and <b>MAY</b> provide other forms of discovery described in Core 3.0 Discovery.
<a href="#">CC-9</a>	OSLC servers <b>MUST</b> provide LDPC creation factories to enable resource creation of Change Management resources via HTTP POST
<a href="#">CC-10</a>	OSLC servers <b>SHOULD</b> provide query capabilities to enable clients to query for resources
<a href="#">CC-11</a>	OSLC query capabilities <b>SHOULD</b> support the OSLC Core Query Syntax and <b>MAY</b> use other query syntax
<a href="#">CC-12</a>	OSLC Services <b>MUST</b> offer delegated UI dialogs (creation and selections) specified via OSLC Core 3.0 Delegated

Clause Number	Requirement
	Dialogs and <b>SHOULD</b> include discovery through a ServiceProvider resource for OSLC v2 compatibility
<a href="#">CC-13</a>	OSLC Services <b>SHOULD</b> offer UI previews for resources that may be referenced by other resources specified via OSLC Core 3.0 Preview and <b>SHOULD</b> include discovery through a server resource for OSLC v2 compatibility
<a href="#">CC-14</a>	OSLC Services <b>SHOULD</b> follow the recommendations for Authentication specified in <a href="#">[OSLCCore3]</a>
<a href="#">CC-15</a>	OSLC Services <b>SHOULD</b> provide error responses using OSLC Core 3.0 defined error formats
<a href="#">CC-16</a>	OSLC servers <b>MUST</b> provide a Turtle representation for HTTP GET requests and <b>SHOULD</b> support Turtle representations on POST and PUT requests.
<a href="#">CC-17</a>	OSLC servers <b>SHOULD</b> provide an RDF/XML representation for HTTP GET requests and <b>SHOULD</b> support RDF/XML representations on POST and PUT requests for compatibility with Change Management 2.0.
<a href="#">CC-18</a>	OSLC servers <b>SHOULD</b> provide a XML representation for HTTP GET, POST and PUT requests that conform to the Core 2.0 Guidelines for XML.
<a href="#">CC-19</a>	OSLC servers <b>MUST</b> provide JSON-LD representations for HTTP GET, POST and PUT requests that conform to the Core Guidelines for JSON-LD
<a href="#">CC-20</a>	OSLC servers <b>SHOULD</b> provide HTML representations for HTTP GET requests
<a href="#">CC-21</a>	CM servers <b>MUST</b> provide Turtle and JSON-LD, and <b>SHOULD</b> provide RDF/XML and XML representations. The XML and JSON representations <b>SHOULD</b> follow the guidelines outlined in the <a href="#">OSLC Core Representations Guidance</a> to maintain compatibility with <a href="#">[OSLCCore2]</a> .
<a href="#">CC-22</a>	CM clients requesting RDF/XML <b>SHOULD</b> be prepared for any valid RDF/XML document. CM clients requesting XML <b>SHOULD</b> be prepared for representations that follow the guidelines outlined in the <a href="#">OSLC Core Representations Guidance</a> .
<a href="#">CC-23</a>	CM servers <b>SHOULD</b> support an [X]HTML representation and a user interface (UI) preview as defined by <a href="#">UI Preview Guidance</a>
<a href="#">CC-24</a>	CM servers <b>MUST</b> accept Turtle and JSON-LD representations and <b>SHOULD</b> accept RDF/XML and XML representations. CM servers accepting RDF/XML <b>SHOULD</b>

Clause Number	Requirement
	be prepared for any valid RDF/XML document. For XML CM servers <b>SHOULD</b> be prepared for representations that follow the guidelines outlined in the <a href="#">OSLC Core Representations Guidance</a> .
<a href="#">CC-25</a>	CM servers <b>MUST</b> provide Turtle and JSON-LD, <b>SHOULD</b> provide RDF/XML, XML, and <b>MAY</b> provide Atom Syndication Format XML representations.
<a href="#">CC-26</a>	<code>text/turtle</code> CM servers <b>MUST</b> respond with Turtle representation.
<a href="#">CC-27</a>	<code>application/ld+json</code> CM servers <b>MUST</b> respond with JSON-LD representation.
<a href="#">CC-28</a>	<code>application/rdf+xml</code> CM servers <b>SHOULD</b> respond with RDF/XML representation without restrictions.
<a href="#">CC-29</a>	<code>application/xml</code> CM servers <b>SHOULD</b> respond with OSLC-defined abbreviated XML representation as defined in the <a href="#">OSLC Core Representations Guidance</a>
<a href="#">CC-30</a>	<code>application/atom+xml</code> CM servers <b>SHOULD</b> respond with Atom Syndication Format XML representation as defined in the <a href="#">OSLC Core Representations Guidance</a>
<a href="#">CC-31</a>	The Atom Syndication Format XML representation <b>SHOULD</b> use RDF/XML representation without restrictions for the <code>atom:content</code> entries representing the resource representations.
<a href="#">CC-32</a>	[ <a href="#">OSLCCore3</a> ] specifies the recommended OSLC authentication mechanisms. In addition to the OSLC Core authentication requirements, OSLC CM servers <b>SHOULD</b> support [ <a href="#">OpenIDConnect</a> ].
<a href="#">CC-33</a>	OSLC CM servers <b>SHOULD</b> support pagination of query results and <b>MAY</b> support pagination of a single resource's properties as defined by [ <a href="#">OSLCCore3</a> ].
<a href="#">CC-34</a>	A client <b>MAY</b> request a subset of a resource's properties as well as properties from a referenced resource. In order to support this behavior a server <b>MUST</b> support the <code>oslc.properties</code> and <code>oslc.prefix</code> URL parameter on a HTTP GET request on individual resource request or a collection of resources by query. If the <code>oslc.properties</code> parameter is omitted on the request, then all resource properties <b>MUST</b> be provided in the response.
<a href="#">CC-35</a>	A client <b>MAY</b> request that a subset of a resource's properties be updated by using the [ <a href="#">LDPPatch</a> ] <code>PATCH</code> method.

Clause Number	Requirement
<a href="#">CC-36</a>	For compatibility with [OSLCCore2], CM servers <b>MAY</b> also support partial update by identifying those properties to be modified using the <code>oslc.properties</code> URL parameter on a HTTP PUT request.
<a href="#">CC-37</a>	If the parameter <code>oslc.properties</code> contains a valid resource property on the request that is not provided in the content, the server <b>MUST</b> set the resource's property to a null or empty value. If the parameter <code>oslc.properties</code> contains an invalid resource property, then a <b>409 Conflict</b> <b>MUST</b> be returned.
<a href="#">CC-38</a>	For multi-valued properties that contain a large number of values, it may be difficult and inefficient to add or remove property values. OSLC CM servers <b>MAY</b> provide support for a partial update of the multi-valued properties as defined by draft specification [LDPPatch]. CM servers <b>MAY</b> also support partial updates through HTTP PUT where only the updated properties are included in the entity request body.
<a href="#">CC-39</a>	[OSLCCM20] introduced State Predicates to define single-value often read-only Boolean properties on a Change Request resource that allow servers to translate their specific status string values into a standard boolean state predicate value. An attempt to update read-only predicates <b>SHOULD</b> be answered with a 409 Conflict HTTP status code. Their presence in a resource representation used for an update via PUT <b>MUST NOT</b> prevent the resource from being updated. Predicates <b>MUST</b> be queryable. The Change Request resource definition sections defines the complete set of predicates.
<a href="#">CC-40</a>	OSLC CM 3.0 provides a similar means of defining a set of standard states that is also extensible. The <code>oslc_cm:state</code> property can have a value of type <code>oslc_cm:State</code> which represents an enumeration of individuals representing a standard set of ChangeRequest states. Servers <b>MAY</b> define additional individuals to extend the states of different ChangeRequest types and lifecycles.
<a href="#">CC-41</a>	<a href="#">OSLC Change Management Version 3.0. Part 2: Vocabulary</a> Defines the vocabulary terms and constraints for OSLC Change Management resources. These terms and constraints are specified according to [OSLCCoreVocab].
<a href="#">CC-42</a>	OSLC CM servers <b>MUST</b> support OSLC Discovery capabilities defined by [OSLCCore3].



Clause Number	Requirement
<a href="#">CC-43</a>	OSLC CM servers <b>MAY</b> provide a ServiceProvider Resource that can be retrieved at a implementation dependent URI.
<a href="#">CC-44</a>	OSLC CM servers <b>MAY</b> provide a ServiceProviderCatalog Resource that can be retrieved at a implementation dependent URI.
<a href="#">CC-45</a>	OSLC CM servers <b>MAY</b> provide a <code>oslc:serviceProvider</code> property for their defined resources that will be the URI to a ServiceProvider Resource.
<a href="#">CC-46</a>	OSLC CM servers <b>MUST</b> supply a value of <code>http://open-services.net/ns/cm#</code> for the property <code>oslc:domain</code> on either <code>oslc:Service</code> or <code>oslc:ServiceProviderCatalog</code> resources.
<a href="#">CC-47</a>	OSLC CM servers <b>MAY</b> allow ChangeRequest state change through [ <a href="#">OSLCActions</a> ].
<a href="#">CC-48</a>	OSLC CM servers <b>MUST</b> support <a href="#">Creation Factories</a> and list them in the Service Provider Resource as defined by OSLC Core. OSLC CM servers <b>SHOULD</b> support Resource Shapes for Creation Factories as defined in [ <a href="#">OSLCShapes</a> ]
<a href="#">CC-49</a>	OSLC CM servers <b>SHOULD</b> support the <a href="#">Query Capabilities</a> as defined by [ <a href="#">OSLCCore3</a> ]. OSLC CM servers <b>SHOULD</b> support Resource Shapes for Query Capability as defined in [ <a href="#">OSLCShapes</a> ]
<a href="#">CC-50</a>	The Query Capability, if supported, <b>MUST</b> support these parameters:
<a href="#">CC-51</a>	If shape information is NOT present with the Query Capability, servers <b>SHOULD</b> use these default properties to contain the result:
<a href="#">CC-52</a>	OSLC CM servers <b>MUST</b> support the selection and creation of resources by delegated web-based user interface dialogs <a href="#">Delegated UIs</a> as defined by [ <a href="#">OSLCCore3</a> ].
<a href="#">CC-53</a>	OSLC CM servers <b>MAY</b> support the pre-filling of creation dialogs based on the definition at <a href="#">Delegated UIs</a> .
<a href="#">CC-54</a>	An OSLC CM server <b>MAY</b> identify or distinguish the usage of various services with additional property values for the <a href="#">OSLC Core</a> defined <code>oslc:usage</code> property on <code>oslc:Dialog</code> , <code>CreationFactory</code> and <code>QueryCapability</code> . The <code>oslc:usage</code> property value of <code>http://open-services.net/ns/core#default</code> will be used to designate the default or primary service to be used by clients when multiple entries are found.

---

## Appendix A. Version Compatibility with 2.0 Specifications

### A.1 Deprecated terms

A number of terms introduced in early development of the OSLC Change Management domain were deprecated in the finalized [OSLCCM20] specification. These terms are summarized here in order to indicate they remain deprecated.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<i>deprecated</i> dcterms:type	zero-or-more	unspecified	String	n/a	n/a	A short string representation for the type, example <i>Defect</i> .
<b>Relationship properties:</b> This grouping of properties are used to identify relationships between resources managed by other OSLC servers						
<i>deprecated</i> oslc_cm:testedByTestCase	zero-or-many	False	Resource	Reference	<i>any</i>	Test case by which this change request is tested. It is likely that the target resource will be an <i>oslc_qm:TestCase</i> , but that is not necessarily the case.
<i>deprecated</i> oslc_cm:affectsTestResult	zero-or-many	False	Resource	Reference	<i>any</i>	Associated QM resource that is affected by this Change Request. It is likely that the target resource will be an <i>oslc_qm:TestResult</i> ,

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
						but that is not necessarily the case.
<i>deprecated</i> oslc_cm:blocksTestExecutionRecord	zero-or-many	False	Resource	Reference	any	Associated QM resource that is blocked by this Change Request. It is likely that the target resource will be an oslc_cm:TestExecutionRecord, but that is not necessarily the case.
<i>deprecated</i> oslc_cm:relatedTestExecutionRecord	zero-or-many	False	Resource	Reference	any	Related to a QM test execution resource. It is likely that the target resource will be an oslc_qm:TestExecutionRecord, but that is not necessarily the case.
<i>deprecated</i> oslc_cm:relatedTestCase	zero-or-many	False	Resource	Reference	any	Related QM test case resource. It is likely that the target resource will be an oslc_qm:TestCase, but that is not necessarily the case.
<i>deprecated</i> oslc_cm:relatedTestPlan	zero-or-many	False	Resource	Reference	any	Related QM test plan resource. It is likely that the target resource will be an oslc_qm:TestPlan, but that is not necessarily the case.
<i>deprecated</i> oslc_cm:relatedTestScript	zero-or-many	False	Resource	Reference	any	Related QM test script resource. It is likely that the target resource will be an oslc_qm:TestScript,

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
						but that is not necessarily the case.

## A.2 Changes from 2.0

The following lists the significant vocabulary changes that were introduced in this specification. The changes are all upward compatible additions and therefore do not introduce incompatibilities with version 2.0.

- Added *oslc\_cm:priority* and *oslc\_cm:severity*
- Added new change management types

---

## Appendix B. Acknowledgements

*This section is non-normative.*

The following individuals have participated in the creation of this specification and are gratefully acknowledged:

**Participants:**

James Amsden, IBM (Editor)  
Geoff Clemm, IBM  
Nick Crossley, IBM (Chair)  
Ian Green, IBM  
Peter Hack, IBM  
David Honey, IBM  
Sam Padget, IBM  
Martin Pain, IBM  
Martin Sarabura, PTC  
Brian Steele, IBM

---

## Appendix C. Change History

*This section is non-normative.*

Revision	Date	Editor	Changes Made
01	06/08/2018	Jim Amsden	Committee Specification 01 Published
02	08/24/2018	Jim Amsden	Includes ReSpec generated Conformance section