



OSLC PROMCODE Version 1.0. Part 3: Constraints

OASIS Standard

11 March 2022

This stage:

<https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/os/promcode-shapes.html> (Authoritative)
<https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/os/promcode-shapes.pdf>

Previous stage:

<https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/cs03/promcode-shapes.html> (Authoritative)
<https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/cs03/promcode-shapes.pdf>

Latest stage:

<https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/promcode-shapes.html> (Authoritative)
<https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/promcode-shapes.pdf>

Latest editor's draft:

<http://tools.oasis-open.org/version-control/browse/wsvn/oslc-promcode/shape/trunk/shape.html>

Technical Committee:

OASIS OSLC Lifecycle Integration for Project Management of Contracted Delivery (OSLC PROMCODE) TC

Chair:

Tom Kamimura (tomkamimura@iCloud.com), Individual

Editors:

Mikio Aoyama (amikio@nanzan.jp), Nanzan University
 Yoshio Horiuchi (hoy@jp.ibm.com), IBM
 Tom Kamimura (tomkamimura@iCloud.com), Individual
 Shinji Matsuoka (matuoka.sinji@jp.fujitsu.com), Fujitsu Limited
 Shigeaki Matsumoto (shigeaki.m@nec.com), NEC Corporation
 Masaki Wakao (wakao@jp.ibm.com), IBM
 Kazuo Yabuta (kazuo.yabuta@gmail.com), Individual
 Hiroyuki Yoshida (yoshida_hiroyuki@nifty.com), Individual

Additional artifacts:

This specification is one component of a Work Product that also includes:

- OSLC PROMCODE Version 1.0. Part 1: Specification. <https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/os/promcode-spec.html>.
- OSLC PROMCODE Version 1.0. Part 2: Vocabulary. <https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/os/promcode-vocab.html>.
- OSLC PROMCODE Version 1.0. Part 3: Constraints (this document). <https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/os/promcode-shapes.html>.
- Machine-readable vocabulary terms: <https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/os/promcode-vocab.ttl>.
- Machine-readable constraints: <https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/os/promcode-shapes.ttl>.

Related work:

This document is related to:

- OSLC PROMCODE Use Cases Version 1.0. Edited by Mikio Aoyama, Yoshio Horiuchi, Tom Kamimura, Shinji Matsuoka, Shigeaki Matsumoto, Masaki Wakao, Kazuo Yabuta, and Hiroyuki Yoshida. Latest stage: <https://docs.oasis-open.org/oslc-promcode/usecase/v1.0/usecase-v1.0.html>.

Abstract:

This document describes the definitions of the OSLC PROMCODE Shape Resources utilizing the OSLC Core Shape Resources. Implementations may use these shapes resources as a basis for their work, providing their own property additions and additional constraints on OSLC defined properties.

Status:

This document was last revised or approved by the membership of OASIS on the above date. The level of approval is also listed above. Check the "Latest stage" location noted above for possible later revisions of this document. Any other numbered Versions and other technical work produced by the Technical Committee (TC) are listed at https://www.oasis-open.org/committees/tc_home.php?wg_abbrev=oslc-promcode#technical.

TC members should send comments on this specification to the TC's email list. Others should send comments to the TC's public comment list oslc-promcode-comment@lists.oasis-open.org, after subscribing to it by following the instructions at the "Send A Comment" button on the TC's web page at https://www.oasis-open.org/committees/tc_home.php?wg_abbrev=oslc-promcode#technical.

Standards Track Work Product

open.org/committees/oslcpromcode/.

This specification is provided under the [RF on Limited Terms](#) Mode of the [OASIS IPR Policy](#), the mode chosen when the Technical Committee was established. For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the TC's web page (<https://www.oasis-open.org/committees/oslcpromcode/ipr.php>).

Note that any machine-readable content ([Computer Language Definitions](#)) declared Normative for this Work Product is provided in separate plain text files. In the event of a discrepancy between any such plain text file and display content in the Work Product's prose narrative document(s), the content in the separate plain text file prevails.

Citation format:

When referencing this specification, the following citation format should be used:

[OSLC-PROMCODE-v1.0-Shapes]

OSLC PROMCODE Version 1.0. Part 3: Constraints. Edited by Mikio Aoyama, Yoshio Horiuchi, Tom Kamimura, Shinji Matsuoka, Shigeaki Matsumoto, Masaki Wakao, Kazuo Yabuta, and Hiroyuki Yoshida. 11 March 2022. OASIS Standard. <https://docs.oasis-open.org/oslcpromcode/promcode/v1.0/os/promcode-shapes.html>. Latest stage: <https://docs.oasis-open.org/oslcpromcode/promcode/v1.0/promcode-shapes.html>.

Notices

Copyright © OASIS Open 2022. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark/> for above guidance.

Table of Contents

- 1. [Introduction](#)
 - 1.1 [Terminology](#)
 - 1.2 [Typographical Conventions and Use of RFC Terms](#)
- 2. [Resource Constraints](#)
 - 2.1 [Artifact](#)
 - 2.2 [IssueCollection](#)
 - 2.3 [Issue](#)
 - 2.4 [ManagedItemCollection](#)
 - 2.5 [ManagedItem](#)
 - 2.6 [Measure](#)
 - 2.7 [Measurement](#)
 - 2.8 [Plan](#)
 - 2.9 [Project](#)
 - 2.10 [Report](#)
 - 2.11 [RiskCollection](#)
 - 2.12 [Risk](#)
 - 2.13 [ScopeItem](#)
 - 2.14 [WorkItem](#)
- 3. [Conformance](#)
- Appendix A. [References](#)
 - A.1 [Normative references](#)

1. Introduction

This section is non-normative.

This specification describes the resource shapes for OSLC PROMCODE resources. PROMCODE introduces the collection of fourteen classes and each resource shape defined in this document corresponds to a class in the collection. Two classes in the collection are used as "abstract" classes. These are `ManagedItem` and `ManagedItemCollection`. The resource shape for `ManagedItem` is a resource that defines common properties of `ScopeItem`, `WorkItem`, `Artifact`, `Issue` and `Risk`, and the resource shape for `ManagedItemCollection` abstracts common properties of `Plan`, `Report`, `RiskCollection` and `IssueCollection`.

As described in [OSLC-Shapes], the representation of a property defined in a resource shape affects the result of a GET request. PROMCODE uses 'inline' representation for two properties, i.e., the representation of the property `targets` of an `Artifact` resource and the representation of the property `observes` of a `Measurement` resource. Both of these properties link the subject resources to `Measure` resources. Even though `Measure` resources are resources, they describe values in a similar way to decimals. Defining the representations of these properties to 'inline' establishes the similarity. It avoids additional network traffic to access the values that would occur if 'reference' representation is used.

1.1 Terminology

This section is non-normative.

Terminology is based on OSLC Core Overview [OSLCCore3], W3C Linked Data Platform [LDP], W3C's Architecture of the World Wide Web [WEBARCH], Hyper-text Transfer Protocol [HTTP11]. Terminology for this specification is defined in part 1 of the multi-part specification.

1.2 Typographical Conventions and Use of RFC Terms

As well as sections marked as non-normative, all authoring guidelines, diagrams, examples, and notes in this specification are non-normative. Everything else in this specification is normative.

The key words **MUST**, **MUST NOT**, **REQUIRED**, **SHOULD**, **SHOULD NOT**, **RECOMMENDED**, **MAY**, and **OPTIONAL** in this specification are to be interpreted as described in [RFC2119].

Conventions

In this section, Resource Shape is represented in RDF+Turtle format. The following common URI prefixes are used throughout this section.

```
@prefix dcterms: <http://purl.org/dc/terms/> .
@prefix oslc: <http://open-services.net/ns/core#> .
@prefix oslc_promcode: <http://open-services.net/ns/promcode#> .
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
@prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
@prefix xml: <http://www.w3.org/XML/1998/namespace> .
@prefix xsd: <http://www.w3.org/2001/XMLSchema#> .
```

2. Resource Constraints

This section specifies the constraints for the PROMCODE resources. The resource properties are not limited to the ones defined in this specification, PROMCODE Servers may provide additional properties. It is recommended that any additional properties exist in their own unique namespace and not use the namespaces defined in these specifications.

2.1 Artifact

An artifact is a work product that is produced in a project. An artifact may be physical or digital.

- **Name:** `Artifact`
- **Type URI:** `http://open-services.net/ns/promcode#Artifact`
- **Summary:** Shape resource of an `Artifact` resource.

Artifact Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for the <code>Artifact</code> resource.
<code>dcterms:isPartOf</code>	Zero-or-one	unspecified	Resource	Reference	<code>oslc_promcode:Artifact</code>	<code>isPartOf</code> is a relation between a child <code>Artifact</code> resource and its parent <code>Artifact</code> resource. An <code>Artifact</code> resource may have multiple child <code>WorkItem</code> resources.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the <code>Artifact</code> resource that is a source of this <code>Artifact</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string of the resource.
<code>oslc_promcode:producedFor</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_promcode:WorkItem</code> , <code>oslc_promcode:ScopeItem</code>	<code>producedFor</code> is a relation between an <code>Artifact</code> resource and a <code>ScopeItem</code> resource or a <code>WorkItem</code> resource. <code>Artifact</code> is produced as a result of implementation of the <code>ScopeItem</code> resources or as a result of the work described by the <code>WorkItem</code> resource.
<code>oslc_promcode:sequenceNumber</code>	Zero-or-one	unspecified	decimal	N/A	Unspecified	A unique number assigned to this resource which represents a position in the sequential order of all <code>Artifact</code> resources of the project.
<code>oslc_promcode:targets</code>	Zero-or-many	unspecified	AnyResource	Inline	<code>oslc_promcode:Measure</code>	<code>targets</code> is a relation between an <code>Artifact</code> resource and a <code>Measure</code> resource. The representation of this property is inline.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.2 IssueCollection

An `IssueCollection` is a resource which is a subclass of `ManagedItemCollection`. An `IssueCollection` only collects `Issues`. All of `Issues` raised in a project should be collected by an `IssueCollection`.

- **Name:** `IssueCollection`
- **Type URI:** `http://open-services.net/ns/promcode#IssueCollection`
- **Summary:** Shape resource of an `IssueCollection` resource.

Standards Track Work Product

IssueCollection Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:date</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	A date on which this <code>IssueCollection</code> resource collects <code>Issue</code> resources.
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier of the resource.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the <code>IssueCollection</code> resource that is a source of this <code>IssueCollection</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string of this <code>IssueCollection</code> resource.
<code>oslc_promcode:belongsTo</code>	Exactly-one	unspecified	Resource	Reference	<code>oslc_promcode:Project</code>	<code>belongsTo</code> is a relation between the <code>IssueCollection</code> resource and a <code>Project</code> resource. An acquirer and a supplier may have multiple projects in operation. The <code>Project</code> resource linked is used to identify the project this <code>IssueCollection</code> resource belongs to.
<code>oslc_promcode:collects</code>	Zero-or-many	unspecified	Resource	Either	<code>oslc_promcode:Issue</code>	<code>collects</code> is a relation between an <code>IssueCollection</code> resource and an <code>Issue</code> resource. An <code>IssueCollection</code> resource collects only <code>Issue</code> resources.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.3 Issue

An issue is a situation that must be resolved in order to meet the objectives of a project. Failure to resolve the situation may result in negative consequences for the project, such as a schedule delay.

- **Name:** `Issue`
- **Type URI:** `http://open-services.net/ns/promcode#Issue`
- **Summary:** Shape resource of an `Issue` resource.

Issue Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the <code>Issue</code> resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for the <code>Issue</code> resource.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the <code>Issue</code> resource that is a source of this <code>Issue</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string for the resource.
<code>oslc_promcode:raisedBy</code>	Zero-or-many	unspecified	Resource	Either	<code>oslc_promcode:Risk</code> , <code>oslc_promcode:Artifact</code> , <code>oslc_promcode:WorkItem</code> , <code>oslc_promcode:ScopeItem</code> , <code>oslc_promcode:Issue</code>	<code>raisedBy</code> is a relation between an <code>Issue</code> resource and other resources of type <code>ScopeItem</code> , <code>WorkItem</code> , <code>Artifact</code> , <code>Risk</code> and <code>Issue</code> . An <code>Issue</code> resource may be raised by one or more resources.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_promcode:raisedDate</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	<code>raisedDate</code> is an optional property of an <code>Issue</code> resource. It is the raised date of the <code>Issue</code> resource. Its value is a <code>dateTime</code> .
<code>oslc_promcode:sequenceNumber</code>	Zero-or-one	unspecified	decimal	N/A	Unspecified	A unique number assigned to this resource which represents a position in the sequential order of all the <code>Issue</code> resources in the project.
<code>oslc_promcode:stateOfIssue</code>	Zero-or-one	unspecified	AnyResource	Either	Unspecified	<code>stateOfIssue</code> is a property that defines the state of an <code>Issue</code> resource. The value is any resource, but is expected to describe its state such as open, action taken, monitored and closed, to represent the state of issue.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.4 ManagedItemCollection

A managed item collection is container of managed items. Any combination of subclass such as a scope item, work item, artifact or issue can be hold in a `ManagedItemCollection` as a snapshot. `ManagedItemCollection` has concrete subclasses such as `Plan`, `Report` and `IssueCollection`.

- **Name:** `ManagedItemCollection`
- **Type URI:** `http://open-services.net/ns/promcode#ManagedItemCollection`
- **Summary:** Shape resource of `ManagedItemCollection`.

ManagedItemCollection Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:date</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	A date on which this <code>ManagedItemCollection</code> resource collects member resources.
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for a <code>ManagedItemCollection</code> resource.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the <code>ManagedItemCollection</code> resource that is a source of this <code>ManagedItemCollection</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string of this <code>ManagedItemCollection</code> resource.
<code>oslc_promcode:belongsTo</code>	Exactly-one	unspecified	Resource	Reference	<code>oslc_promcode:Project</code>	<code>belongsTo</code> is a relation between the <code>ManagedItemCollection</code> resource and a <code>Project</code> resource.
<code>oslc_promcode:collects</code>	Zero-or-many	unspecified	Resource	Either	<code>oslc_promcode:Issue</code> , <code>oslc_promcode:Risk</code> , <code>oslc_promcode:Artifact</code> , <code>oslc_promcode:WorkItem</code> , <code>oslc_promcode:ScopeItem</code>	<code>ManagedItem</code> resources included in this <code>ManagedItemCollection</code> . A <code>ManagedItemCollection</code> resource collects resources of type <code>ScopeItem</code> , <code>WorkItem</code> , <code>Artifact</code> , <code>Risk</code> , and <code>Issue</code> .
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.5 ManagedItem

A managed item is a scope item, work item, artifact, issue, or some other entity that is part of a project. Managed item resources use `dcterms:type` to specify concrete subclasses. This practice is deprecated in OSLC Core 3.0.

- **Name:** `ManagedItem`
- **Type URI:** `http://open-services.net/ns/promcode#ManagedItem`

Standards Track Work Product

- **Summary:** Shape resource for `ManagedItem`.

ManagedItem Properties

Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for a <code>ManagedItem</code> resource.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the <code>ManagedItem</code> resource that is a source of this <code>ManagedItem</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string for a <code>ManagedItem</code> resource.
<code>oslc_promcode:sequenceNumber</code>	Zero-or-one	unspecified	decimal	N/A	Unspecified	A unique number assigned to the resource which represents a position in the sequential order of resources of the same type of <code>ManagedItem</code> .
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.6 Measure

A measure is an observation of some measurable aspect of an artifact.

- **Name:** `Measure`
- **Type URI:** `http://open-services.net/ns/promcode#Measure`
- **Summary:** Shape resource of a `Measure` resource

Measure Properties

Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for the <code>Measure</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string of this <code>Measure</code> resource.
<code>oslc_promcode:metricOfMeasure</code>	Zero-or-one	unspecified	AnyResource	Either	Unspecified	<code>metricOfMeasure</code> is a property that defines a metric of measure of this resource. The value is any resource, but is expected to have information on the metric of this <code>Measure</code> resource.
<code>oslc_promcode:unitOfMeasure</code>	Zero-or-one	unspecified	AnyResource	Either	Unspecified	<code>unitOfMeasure</code> is a property that defines a unit of measure of this <code>Measure</code> resource. The value is any resource, but is expected to have information on the unit of measure of this <code>Measure</code> resource, describing whether the metric is a rate, a ratio, a quantity, a time, etc.
<code>oslc_promcode:valueOfMeasure</code>	Exactly-one	unspecified	decimal	N/A	Unspecified	<code>valueOfMeasure</code> is a property that represents a value for the <code>Measure</code> resource.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.7 Measurement

A measurement measures some aspect of an artifact at some point in time.

- **Name:** `Measurement`
- **Type URI:** `http://open-services.net/ns/promcode#Measurement`
- **Summary:** Shape resource of a `Measurement` resource

Measurement Properties

Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:date</code>	Exactly-one	unspecified	dateTime	N/A	Unspecified	<code>date</code> is a property of a <code>Measurement</code> resource. It is the date on which the measurement was made.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for the <code>Measurement</code> resource.
<code>oslc_promcode:measures</code>	Exactly-one	unspecified	Resource	Reference	<code>oslc_promcode:Artifact</code>	<code>measures</code> is a relation between a <code>Measurement</code> resource and an <code>Artifact</code> resource. The measurement represented by the resource is on the artifact represented by the <code>Artifact</code> resource.
<code>oslc_promcode:observes</code>	Zero-or-many	unspecified	AnyResource	Inline	<code>oslc_promcode:Measure</code>	<code>observes</code> is a relation between a <code>Measurement</code> resource and a <code>Measure</code> resource. One <code>Measurement</code> resource observes zero or many <code>Measure</code> resources. The representation of this property is inline.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.8 Plan

A Plan is a resource which is a subclass of `ManagedItemCollection` to describe a plan, which is agreed between an acquirer and a supplier at project initiation. A plan consists of `ScopeItems`, `WorkItems`, `Artifacts`, `Targets` and `Measures`.

- **Name:** `Plan`
- **Type URI:** `http://open-services.net/ns/promcode#Plan`
- **Summary:** Shape resource of a `Plan` resource

Plan Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:date</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	A date on which this <code>Plan</code> resource collects member resources.
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for a <code>Plan</code> resource.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the <code>Plan</code> resource that is a source of this <code>Plan</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string of this <code>Plan</code> resource.
<code>oslc_promcode:belongsTo</code>	Exactly-one	unspecified	Resource	Reference	<code>oslc_promcode:Project</code>	<code>belongsTo</code> is a relation between a <code>Plan</code> resource and a <code>Project</code> resource.
<code>oslc_promcode:collects</code>	Zero-or-many	unspecified	Resource	Either	<code>oslc_promcode:Artifact</code> , <code>oslc_promcode:WorkItem</code> , <code>oslc_promcode:ScopeItem</code>	<code>collects</code> is a relation between a <code>Plan</code> resource and resources, where each linked resource from the <code>Plan</code> resource is a <code>ScopeItem</code> resource, a <code>WorkItem</code> resource or an <code>Artifact</code> resource.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.9 Project

A project is software development work to achieve some business goal.

- **Name:** `Project`
- **Type URI:** `http://open-services.net/ns/promcode#Project`
- **Summary:** Shape resource of a `Project` resource.

Project Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property of a <code>Project</code> resource to help a human understand the project.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for a <code>Project</code> resource.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the <code>Project</code> resource that is a source of this <code>Project</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string for a <code>Project</code> resource.
<code>oslc_promcode:actualEndDate</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	<code>actualEndDate</code> is a property of a <code>Project</code> resource that describes actual end date of the project. Its value is of type <code>xsd:dateTime</code> .
<code>oslc_promcode:actualStartDate</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	<code>actualStartDate</code> is a property of a <code>Project</code> resource. It is the actual start date of the project. Its value is of type <code>xsd:dateTime</code> .
<code>oslc_promcode:metricOfScopeItemSize</code>	Zero-or-one	unspecified	AnyResource	Either	Unspecified	<code>metricOfScopeItemSize</code> is a property that describes a metric of properties of <code>plannedSize</code> and <code>actualSize</code> of <code>ScopeItem</code> . The value can be any resource, but it is expected to have information on the desired metric for all the <code>ScopeItem</code> resources of the project.
<code>oslc_promcode:plannedEndDate</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	<code>plannedEndDate</code> is a property of a <code>Project</code> resource. It is the planned end date of the project. Its value is of type <code>xsd:dateTime</code> .
<code>oslc_promcode:plannedStartDate</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	<code>plannedStartDate</code> is a property of a <code>Project</code> resource. It is the planned start date of the project. Its value is of type <code>xsd:dateTime</code> .
<code>oslc_promcode:unitOfScopeItemSize</code>	Zero-or-one	unspecified	AnyResource	Either	Unspecified	<code>unitOfScopeItemSize</code> is a property that describes a unit of size of properties of <code>plannedSize</code> and <code>actualSize</code> of <code>ScopeItem</code> . The value can be any resource, but it is expected to have information on the desired unit of size, describing whether the metric is a rate, a ratio, a quantity, a time, and so on for all the <code>ScopeItem</code> resources in the project.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.10 Report

A Report is a resource which is a subclass of `ManagedItemCollection` to describe a report. A Report is associated to corresponding Plan.

- **Name:** `Report`
- **Type URI:** `http://open-services.net/ns/promcode#Report`
- **Summary:** Shape resource of a `Report` resource

Report Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:date</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	A date on which this Report resource collects member resources.
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for a Report resource.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the Report resource that is a source of this Report resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string of this Report resource.
<code>oslc_promcode:belongsTo</code>	Exactly-one	unspecified	Resource	Reference	<code>oslc_promcode:Project</code>	<code>belongsTo</code> is a relation between this Report resource and a Project resources.
<code>oslc_promcode:collects</code>	Zero-or-many	unspecified	Resource	Either	<code>oslc_promcode:Artifact</code> , <code>oslc_promcode:WorkItem</code> , <code>oslc_promcode:ScopeItem</code>	<code>collects</code> is a relation between the Report resource and resources, where each linked resource from the Plan resource is a ScopeItem resource, a Workitem resource or an Artifact resource. The Report resource collects a subset of resources collected by the Plan resource that is linked by <code>correspondsTo</code> property.
<code>oslc_promcode:correspondsTo</code>	Zero-or-one	unspecified	Resource	Reference	<code>oslc_promcode:Plan</code>	<code>correspondsTo</code> is a relation between a Report resource and a Plan resource. A Report resource has at most one <code>correspondsTo</code> relation to the corresponding a Plan resource. If a plan is changed and a new Plan resource is created, the Report may need to be linked to the new Plan resource.
<code>oslc_promcode:includes</code>	Zero-or-many	unspecified	Resource	Either	<code>oslc_promcode:Measurement</code>	<code>includes</code> is a relation between this Report resource and Measurement resources. A Measurement resource linked by <code>includes</code> from this resource must measure an Artifact resource that is linked by <code>collects</code> property of this Report resource.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.11 RiskCollection

- **Name:** `RiskCollection`
- **Type URI:** `http://open-services.net/ns/promcode#RiskCollection`
- **Summary:** Shape resource of a `RiskCollection` resource.

RiskCollection Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:date</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	A date on which this <code>RiskCollection</code> resource collects member resources.
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for a <code>RiskCollection</code> resource.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the <code>RiskCollection</code> resource that is a source of this <code>RiskCollection</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string of this <code>RiskCollection</code> resource.
<code>oslc_promcode:belongsTo</code>	Exactly-one	unspecified	Resource	Reference	<code>oslc_promcode:Project</code>	<code>belongsTo</code> is a relation between the <code>RiskCollection</code> resource and a <code>Project</code> resource.
<code>oslc_promcode:collects</code>	Zero-or-many	unspecified	Resource	Either	<code>oslc_promcode:Risk</code>	<code>collects</code> is a relation between a <code>RiskCollection</code> resource and a <code>Risk</code> resource.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.12 Risk

- **Name:** `Risk`
- **Type URI:** `http://open-services.net/ns/promcode#Risk`
- **Summary:** Shape resource of a `Risk` resource.

Risk Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human to understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for a <code>Risk</code> resource.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the <code>Risk</code> resource that is a source of this <code>Risk</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string for a <code>Risk</code> resource.
<code>oslc_promcode:identifiedBy</code>	Zero-or-many	unspecified	Resource	Either	<code>oslc_promcode:Issue</code> , <code>oslc_promcode:Artifact</code> , <code>oslc_promcode:WorkItem</code> , <code>oslc_promcode:ScopeItem</code> , <code>oslc_promcode:Risk</code>	<code>identifiedBy</code> is a relation between a <code>Risk</code> resource and a resource of type <code>ScopeItem</code> , <code>WorkItem</code> , <code>Artifact</code> , <code>Risk</code> or <code>Issue</code> . A <code>Risk</code> resource may be identified by one or more resources.
<code>oslc_promcode:identifiedDate</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	<code>identifiedDate</code> is the date on which the risk was identified.
<code>oslc_promcode:sequenceNumber</code>	Zero-or-one	unspecified	decimal	N/A	Unspecified	A unique number assigned to this resource which represents a position in the sequential order of all the <code>Risk</code> resources of the project.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_promcode:stateOfRisk</code>	exactly-one	unspecified	AnyResource	Either	Unspecified	<code>stateOfRisk</code> is a property that defines the state of a <code>Risk</code> resource. The value is any resource, but is expected to describe its state such as open, action taken, monitored and closed, to represent the state of the risk.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.13 ScopeItem

A `ScopeItem` defines the work to be included in or excluded from a project. It defines the boundaries of the project.

- **Name:** `ScopeItem`
- **Type URI:** `http://open-services.net/ns/promcode#ScopeItem`
- **Summary:** Shape resource of a `ScopeItem` resource

ScopeItem Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for a <code>ScopeItem</code> resource.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the <code>ScopeItem</code> resource that is a source of this <code>ScopeItem</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string for a <code>ScopeItem</code> resource.
<code>oslc_promcode:actualSize</code>	Zero-or-one	unspecified	decimal	N/A	Unspecified	<code>actualSize</code> is a property for actual development size for a <code>ScopeItem</code> resource.
<code>oslc_promcode:isPartOf</code>	Zero-or-one	unspecified	Resource	Reference	<code>oslc_promcode:ScopeItem</code>	<code>isPartOf</code> is a relation between a child <code>ScopeItem</code> resource and its parent <code>ScopeItem</code> resource. A <code>ScopeItem</code> resource may have multiple child <code>ScopeItem</code> resources.
<code>oslc_promcode:plannedSize</code>	Zero-or-one	unspecified	decimal	N/A	Unspecified	<code>plannedSize</code> is a property for estimated development size for a <code>ScopeItem</code> resource.
<code>oslc_promcode:sequenceNumber</code>	Zero-or-one	unspecified	decimal	N/A	Unspecified	A unique number assigned to this resource which represents a position in the sequential order of all the <code>ScopeItem</code> resources of the project.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

2.14 WorkItem

A work item describes work to be performed in a project delivery contract. It adds detail to the description of work that is described by a scope item. These details typically include cost, schedule, and resource requirements. The set of all work items in a project form a work breakdown structure.

- **Name:** `WorkItem`
- **Type URI:** `http://open-services.net/ns/promcode#WorkItem`
- **Summary:** Shape resource of a `WorkItem` resource

WorkItem Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:description</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	<code>dcterms:description</code> is a property to help a human understand the resource.
<code>dcterms:identifier</code>	Exactly-one	unspecified	string	N/A	Unspecified	A unique identifier for the <code>WorkItem</code> resource.
<code>dcterms:source</code>	Zero-or-one	unspecified	string	N/A	Unspecified	A string that identifies the <code>WorkItem</code> resource that is a source of this <code>WorkItem</code> resource.
<code>dcterms:title</code>	Zero-or-one	unspecified	XMLLiteral	N/A	Unspecified	A title string for the <code>WorkItem</code> resource.
<code>oslc_promcode:actualEndDate</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	<code>actualEndDate</code> is a property of a <code>WorkItem</code> resource. It is the actual end date of the work item. Its value is of type <code>xsd:dateTime</code> .
<code>oslc_promcode:actualStartDate</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	<code>actualStartDate</code> is a property of a <code>WorkItem</code> resource. It is the actual start date of the work item. Its value is of type <code>xsd:dateTime</code> .
<code>oslc_promcode:isPartOf</code>	Zero-or-one	unspecified	Resource	Reference	<code>oslc_promcode:WorkItem</code>	<code>isPartOf</code> is a relation between a child <code>WorkItem</code> resource and its parent <code>WorkItem</code> resource. A <code>WorkItem</code> resource may have multiple child <code>WorkItem</code> resources.
<code>oslc_promcode:plannedEndDate</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	<code>plannedEndDate</code> is a property of a <code>WorkItem</code> resource. It is the planned end date of the work item. Its value is of type <code>xsd:dateTime</code> .
<code>oslc_promcode:plannedStartDate</code>	Zero-or-one	unspecified	dateTime	N/A	Unspecified	<code>plannedStartDate</code> is a property of <code>WorkItem</code> resource. It is the planned start date of the work item. Its value is of type <code>xsd:dateTime</code> .
<code>oslc_promcode:representedBy</code>	Zero-or-one	unspecified	AnyResource	Either	Unspecified	<code>representedBy</code> is a relation between the <code>WorkItem</code> resource and a resource that represents a person responsible for the progress of the work described by this resource. The value is any resource, but is expected to describe a person such as a <code>foaf:Person</code> resource.
<code>oslc_promcode:requiredBy</code>	Zero-or-many	unspecified	Resource	Reference	<code>oslc_promcode:Artifact</code> , <code>oslc_promcode:ScopeItem</code>	<code>requiredBy</code> is a relation between this <code>WorkItem</code> resource and a <code>ScopeItem</code> resource or an <code>Artifact</code> resource.
<code>oslc_promcode:sequenceNumber</code>	Zero-or-one	unspecified	decimal	N/A	Unspecified	A unique number assigned to this resource which represents a position in the sequential order of all the <code>WorkItem</code> resources of the project.
<code>rdf:type</code>	One-or-many	unspecified	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

3. Conformance

PROMCODE servers **MUST** follow the constraints defined here where required, and with the meanings defined here.

PROMCODE servers **MAY** provide additional constraints for specific purposes.

Appendix A. References

A.1 Normative references

[HTTP11]

R. Fielding, Ed.; J. Reschke, Ed.. *Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing*. June 2014. Proposed Standard. URL: <https://httpwg.org/specs/rfc7230.html>

[LDP]

Steve Speicher; John Arwe; Ashok Malhotra. *Linked Data Platform 1.0*. 26 February 2015. W3C Recommendation. URL: <https://www.w3.org/TR/ldp/>

[OSLC-Shapes]

Arthur Ryman; Jim Amsden. *OSLC Core Version 3.0. Part6: Resource Shapes*. URL: <https://docs.oasis-open-projects.org/oslc-op/core/v3.0/resource-shape.html>

[OSLCCore3]

Jim Amsden; Martin Sarabura. *OSLC Core 3.0*. URL: <https://docs.oasis-open-projects.org/oslc-op/core/v3.0/oslc-core.html>

[RFC2119]

S. Bradner. *Key words for use in RFCs to Indicate Requirement Levels*. March 1997. Best Current Practice. URL: <http://www.ietf.org/rfc/rfc2119.txt>

[WEBARCH]

Ian Jacobs; Norman Walsh. *Architecture of the World Wide Web, Volume One*. 15 December 2004. W3C Recommendation. URL: <https://www.w3.org/TR/webarch/>